

DESIG	#	DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECK	ED	APPROVED_	DRAWING NO.	REV. A
	A	de	DSI 9285 SHEET	1 OF 1
DATE			TITLE	SCALE
04.08.20			INSTALLATION OF STRUT ASSEMBLY	NTS
Α		04.08.20	NEW ISSUE	

DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS IIN-D350-636 REV. C

REF. CANADIAN STC: SH99-7 REF. FAA STC: SR00646SE

It is acceptable to perform AS355 SB 01.15 to the Dart D350-636-011/-012 skidtubes in order to install the 355A84-0522-00 strut assembly that is required with the flotation system. Caution must be exercised when drilling through the Dart skidtube as holes must also be drilled through the web in the middle of the Dart skidtube. Holes should be deburred and touched up with alodine per MIL-C-5541 and primer per MIL-P-85582 or MIL-P-23377 before installing the 355A84-0521-22/-23 supports.




Figure 1 - Installation of Strut Assembly, Skidtube Cross-section (REF)

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-0-01

APPROVED

BY:
D. SHEPHERD (DE # 02)

DATE:
CERT. NO.:
SH99-7
ISSUE NO.:
1

Copyright © 2004 by DART AEROSPACE LTD